



A diagram of a circular object, possibly a lens or a component, with four numbered points (1, 2, 3, 4) indicating specific locations. The object is surrounded by a square frame with four corner markers, each consisting of a small circle with a crosshair.

A diagram of a circular hole with 7 internal holes and 4 corner holes. The internal holes are numbered 1 through 7. The corner holes are numbered 8 through 11. The diagram is used to illustrate the layout of the holes for the test.

对接电机连接器型号				
连接器		动力连接器	增量式编码器连接器	绝对式编码器连接器
航插头		YD32K4TSJ	YD28K15TSJ	YD28K7TSJ

额定电压	380	V AC
额定功率	4.5	KW
额定转矩	21.5	N • m
最大转矩	53	N • m
额定转速	2000	RPM
最大转速	2400	RPM
额定电流	9.5	A
最大电流	23	A
线反电势系数	140±10%	V/KRPM
线电阻	0.88±10%	Ω
线电感	4±10%	mH
转动惯量	79.6±10%	10 ⁻⁴ kg•m ²
极对数	4	对
电机绝缘等级	Class F	
电机防护等级	IP65	

					 WECON® 维控科技				版 本
									A0
					型号	阶段标记	重要度	重 量	比 例
标记处数	更改文件号	签 名	日期						
设 计		标准	化		WE180M-45020T-D2F	第 1 张		共 1 张	
校 对		审 定							
审 核		批 准							
工 艺		日 期							