



A diagram of a circular component, likely a lens or a sensor, with four numbered points (1, 2, 3, 4) indicating specific locations. The component is overlaid with a red crosshair. The points are located at the intersections of the crosshair with the component's boundary: 1 is at the top, 2 is on the left, 3 is on the right, and 4 is at the bottom.

对接电机连接器型号				
连接器		动力连接器	增量式编码器连接器	绝对式编码器连接器
航插头		YD32K4TSJ	YD28K15TSJ	YD28K7TSJ

额定电压	380	V AC
额定功率	4.3	KW
额定转矩	27	N • m
最大转矩	67	N • m
额定转速	1500	RPM
最大转速	1800	RPM
额定电流	10	A
最大电流	25	A
线反电势系数	172±10%	V/KRPM
线电阻	0.87±10%	Ω
线电感	5.5±10%	mH
转动惯量	96.4±10%	10 ⁻⁴ kg•m ²
极对数	4	对
电机绝缘等级	Class F	
电机防护等级	IP65	

					 WELCON® 维控科技				版 本
									A0
					型号	阶段标记	重要度	重 量	比 例
标记	处数	更改文件号	签 名	日期					
设 计			标准		WE180M-43015T-D2F	第 1 张		共 1 张	
校 对			审 定						
审 核			批 准						
工 艺			日 期						